



#0169

Breakaway

NON-AMMONIATED STRIPPER

DESCRIPTION:

Use BREAKAWAY for removal-stripping of Wax, Wax-Resin Blends, Polymers, Acrylics, Styrenes, Rebons, Dual Polymers, Cross linked waxes and Synthetic Finishes. PH 13, water thin, 100% miscible in water, soft, hard, hot or cold.

WHY IS IT USED?

- Designed especially for removing detergent-resistant, metal cross-link floor finishes
- Removes ANY type of water emulsion floor coating
- Will work with any system, mop and bucket, floor machine, and automatic scrubbers, as well as spraying.
- Specifically formulated as a floor coating stripper – works fast even on heavy old films
- Low foam – Biodegradable
- Ideal where no ammonia odors are desired



HOW IS IT USED?

1. Dilute 8oz to 32oz of BREAKAWAY per gallon of cold or hot water.
2. Be sure to wet surface completely. Do NOT prepare an area larger than you can scrub while surface is wet.
3. Keep solution wet on surface as long as possible. This will break your link' system, making complete removal easy. Agitate with floor machine, brush, or pad. Re-wet if necessary during scrubbing period.
4. Pick up solution with vacuum or mop. Re-wet if surface becomes dry BEFORE picking up.
5. Rinse with clear, clean, cold water. If white residue appears, or if the floor is very porous, – rinse using 2 ounces of #8250 FREEDOM per gallon cold water – final rinse with clear water.

NOTE: This product is never to be used in a daily mopping program because stripping will start at once in any dilution ratio.

PACKAGING:

This product is available in single gallons, 4- 1 gallon/cases, 5 gallon pails, and 55 gallon drums.

May 22, 2023