



#0411

Everlasting

WHEN YOUR BUILDING'S FLOORS NEED AN EVERLASTING SHINE & DURABILITY

DESCRIPTION:

A unique polymer engineered by a polymerization procedure which provides the absolute ultimate gloss in water-based floor finishes. EVERLASTING is for all resilient floors: vinyl, asphalt, tile, vinyl asbestos, concrete, marble, rubber, linoleum, and terrazzo.

WHAT DOES IT DO?

Provides the highest gloss and resistance to wear with minimal labor required. EVERLASTING works well in any maintenance program. EVERLASTING can buff or burnish to a brilliant gloss with electric or propane powered programs.

HOW IS IT USED?

1. FLOOR PREPARATION: For best results, floor should be stripped of all old finishes before applying #0411 EVERLASTING.
 - a. Use floor stripper #0166 HYPER STRIP, #0168 MELTDOWN or #0169 BREAKAWAY in hot water for best results.
 - b. Machine scrub with black stripping pad.
 - c. Pick up old finish with wet vacuum.
 - d. Immediately rinse floor with neutralizer and follow with 2 fresh water rinses.
2. APPLICATION: Use only new wax mops (soaked in cold water) with clean buckets/wringers.
 - a. Apply 4-5 coats (to unsealed floor) evenly using medium to thin coats.
 - i. If the floor is an old, worn, porous floor; seal floor with #0475 SEAL KOTE, before applying finish.
 - b. Allow 45 minutes dry time between coats. (In extremely humid weather conditions, it is recommended that a dry time of 2 hours or more be allowed to avoid tearing the finish).



Coverage is 1,500-2,500 square feet per gallon.

Maintenance

1. DUST MOP DAILY.
2. DAMP MOP THE FLOOR – EVERLASTING can be damp mopped with #0185 MAGNIFICENT SEVEN or machine scrubbed with #0199 G-P CONCENTRATE.
3. SPRAY AND DRY BUFFING – EVERLASTING can be buffed for removal of scuffs and traffic marks. For light soil areas, dry buffing is sufficient; for areas such as entrances and stairways, use #0191 BEYOND spray solution.

PACKAGING:

This product is available in single gallons, 4- 1 gallon/cases, 5 gallon pails, and 55 gallon drums.

May 19, 2023



www.alco-chem.com

North: 45 N. Summit St. | Akron, OH 44308 | P: 330.253.3535 | 1.800.589.ALCO | F: 330.253.9219
South: 1303 Park Ave. SW | Canton, OH 44706 | P: 330.833.8551 | 1.800.437.5248 | F: 330.833.0011