

Solutions for a Cleaner Environment

# #0442 Stampede

**OPTIMUM GLOSS & RESISTANCE TO WEAR** 

## **DESCRIPTION:**

A group of modified polymers engineered by a polymerization procedure which provides the ultimate product in water-based floor finishes for shine and durability. STAMPEDE provides thermoplastic action when burnished at ultra-high speeds.

## WHERE IS IT USED?

STAMPEDE is for all resilient floors:

- Vinyl
- Asphalt
- Tile
- Vinyl Asbestos
- Concrete
- 1. FLOOR PREPARATION: For best results, floor should be stripped of all old finishes before applying #0442 STAMPEDE.
  - a. Use floor stripper #0166 HYPER STRIP, #0168 MELTDOWN or #0169 BREAKAWAY in hot water for best results.
  - b. Machine scrub with black stripping pad.
  - c. Pick up old finish with wet vacuum.
  - d. Immediately rinse floor with neutralizer and follow with 2 fresh water rinses.
- 2. APPLICATION: Use only new wax mops (soaked in cold water) with clean buckets/wringers.
  - a. Use medium to thin coats, applied evenly.
    - i. If the floor is an old, worn, porous floor, seal floor with #0475 SEAL KOTE before applying finish.
  - b. Apply 4-5 coats of STAMPEDE. Allow 45 minutes dry time between coats.
    - i. In extremely humid weather conditions, it is recommended that a dry time of 2 hours or more be allowed to avoid tearing the finish.

#### Coverage is 1,500-2,500 square feet per gallon.

**HOW IS IT USED?** 

Terrazzo

Marble Rubber Linoleum



Page 1 of 2

#### Maintenance

- 1. DUST MOP DAILY.
- 2. DAMP MOP THE FLOOR STAMPEDE can be damp mopped with #0185 MAGNIFICENT SEVEN or machine scrubbed with #0199 G-P CONCENTRATE or any of Alco's neutral disinfectants (like DC-7 or WINTAFECT).
- 3. SPRAY AND DRY BUFFING STAMPEDE can be buffed for removal of scuffs and traffic marks. For light soil areas, dry buffing is sufficient; for areas such as entrances and stairways, use #0191 BEYOND spray solution.

### **PACKAGING:**

This product is available in single gallons, 4-1 gallon/cases, 5 gallon pails, and 55 gallon drums.



May 19, 2023

www.alco-chem.com

North: 45 N. Summit St. | Akron, OH 44308 | P: 330.253.3535 | 1.800.589.ALCO | F: 330.253.9219 South: 1303 Park Ave. SW | Canton, OH 44706 | P: 330.833.8551 | 1.800.437.5248 | F: 330.833.0011