

Solutions for a Cleaner Environment

#0498 Trifecta

A TRIPLE WINNER: EXTREME DURABILITY, OPTIMUM GLOSS, REMARKABLE SCUFF MARK RESISTANCE

DESCRIPTION:

A revolutionary polymer engineered through advancements in the acrylic, urethane and cross-linking systems and procedures. TRIFECTA provides the ultimate in gloss and toughness in water-based floor finish.

WHAT DOES IT DO?

TRIFECTA provides high gloss and minimal wear with very little labor required. TRIFECTA works well in any maintenance program. This product can be buffed or high-speed burnished with electric or propane- powered programs to a brilliant gloss that has been previously unattainable, with up to 30-40% higher gloss than conventional finishes. TRIFECTA is also formulated to increase surface hardness, making it resistant to traffic wear, scuffing and black heel marks.



Page **1** of **2**

HOW IS IT USED?

- 1. FLOOR PREPARATION: For best results, floor should be stripped of all old finishes before applying #0411 EVERLASTING.
 - a. Use floor stripper #0166 HYPER STRIP, #0168 MELTDOWN or #0169 BREAKAWAY in hot water for best results.
 - b. Machine scrub with black stripping pad.
 - c. Pick up old finish with wet vacuum.
 - d. Immediately rinse floor with neutralizer and follow with 2 fresh water rinses.
- 2. APPLICATION: Use only new wax mops (soaked in cold water) with clean buckets/wringers.
 - a. Apply 4-5 coats (to unsealed floor) evenly using medium to thin coats.
 - i. If the floor is an old, worn, porous floor; seal floor with #0475 SEAL KOTE, before applying finish.
 - b. Allow 45 minutes dry time between coats. (In extremely humid weather conditions, it is recommended that a dry time of 2 hours or more be allowed to avoid tearing the finish).

Coverage is 1,500-2,500 square feet per gallon.

Maintenance

- 1. DUST MOP DAILY.
- 2. DAMP MOP THE FLOOR TRIFECTA can be damp mopped with #0185 MAGNIFICENT SEVEN or machine scrubbed with #0199 G-P CONCENTRATE or any of Alco's neutral disinfectants (like DC-7 or WINTAFECT) without harming finish.
- 3. SPRAY AND DRY BUFFING TRIFECTA can be buffed for removal of scuffs and traffic marks. Mop floors with #0195 CLEAN 'N SHINE or #0191 BEYOND. Allow to dry before burnishing. For spraying buffing, use #0429-QT BUFF STUFF.

PACKAGING:

This product is available in single gallons, 4-1 gallon/cases, 5 gallon pails, and 55 gallon drums.



May 26, 2023

www.alco-chem.com

North: 45 N. Summit St. | Akron, OH 44308 | P: 330.253.3535 | 1.800.589.ALCO | F: 330.253.9219 South: 1303 Park Ave. SW | Canton, OH 44706 | P: 330.833.8551 | 1.800.437.5248 | F: 330.833.0011